

SKIVED PTFE SHEET

.001" to .250" thick

Thickness, Tolerances and Weight Per Square Foot

Thickness (Inches)	Tolerance +/- (Inches)	Lbs. Per Square Foot (12" x 12")
.001	.0003	.012
.002	.0003	.024
.003	.0005	.036
.004	.0005	.048
.005	.0005	.060
.010	.001	.120
.015	.001	.180
.020	.0015	.240
.025	.0015	.300
.032	.002	.360
.062	.005	.720
.093	.005	1.120
.125	.010	1.500
.187	.015	2.250
.250	.020	3.000

Standard Widths

12", 24", 36", 48"
Up to 72" wide


Material Types:

Virgin, Reprocessed,
Enflon® (filled PTFE),
Virgin & Filled Modified PTFE

**Consult sales office
for additional information.**

Etching

Sodium-Ammonia Etching available
for adhering PTFE to another surface.
Etched one-side or two-sides.



Skived PTFE Sheet



Molded PTFE Cylinder



Molded PTFE Rod



Skived PTFE Tape



Pressure Sensitive PTFE Tape



Extruded PTFE Tubing



Extruded PTFE Rod



Molded PTFE Sheet



Enflon® Filled PTFE



ENFLO

ENFLO LLC
315 Lake Avenue
Bristol, CT 06010
Tel. **860-589-0014**
Fax **860-589-7179**
Toll Free **1-888-887-4093**

ENFLO CANADA LTD.
73 Industrial Road
Grand Falls, NB E3Y 3V1
Tel. **506-473-3711**
Fax **506-473-2307**
Toll Free **1-800-561-0050**

Email us at ptfe@enflo.com
Visit us at www.enflo.com